

GARAGES – STANDARD OF FINISH

STANDARD GARAGE WITHOUT FOUNDATIONS
EXTERNAL WALL
Render, colour white
Thermal insulation, facade polystyrene 50 mm
OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm ¹
Timber studs (resinous wood) 120 mm
EXTERNAL WALL CLOSE TO HOUSE'S WALL
OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm ¹
Timber studs (resinous wood) 120 mm
INTERNAL WALL
OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm ¹
Timber studs (resinous wood) 120 mm
EAVES CLADDING
Timber cladding, colour white
PENT /GABLE /HIPPED ROOF
Cement roof tiles according to the samples ²
Roof battens
Counter battens
Breathable membrane
Timber rafters/trusses (according to the static calculations)
OSB sterling boards/chipboards 22 mm, with access opening
FLAT ROOF
EPDM
Tapered panels of mineral wool
OSB sterling boards/chipboards 22 mm
Timber joists 220 mm
Battens
GUTTERING
PVC gutters and down pipes, colour white
GARAGE DOOR
Single garage: sectional garage door, manual drive, woodgrain finish, according to the samples, 2500 x 2125 mm, colour white
Double garage: sectional garage door, automatic, woodgrain finish, according to the samples, 5000 x 2125 mm, colour white (if drawn on plans)
GARAGE SIDE DOOR
Colour white (if drawn on plans)

OPTIONS
OPTION 1
Shelves between timber studs on external and internal walls
OPTION 2A
Electrical installation for a garage integrated with the house: 2 ceiling cable outlets with 1 two-way switch, 2 single electric sockets.
OPTION 2B
Electrical installation for a detached garage: 2 ceiling cable outlets with 1 two-way switch, 2 single electric sockets, 6 way consumer unit, electrical cable between house and garage (distance between outlets in foundation - max 10 m) with connection. Notes: Customer is responsible for supply and installation of electrical cable duct between house and garage. Electrical equipment in garage can differ from the one installed in a house.
OPTION 3
Electric drive for garage gate 2500 x 2125 mm
OPTION 4
Door between house and garage
OPTION 5
Internal linings (for garages larger than 40 m ² included in the price)
EXTERNAL WALL
Insulation - mineral wool (between wall studs)- 120 mm
OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm ¹
Plasterboard - 12.5 mm
PENT /GABLE /HIPPED ROOF
Mineral wool above bottom chord truss 220 mm
Plasterboard - 12.5 mm
with folding loft ladder to attic area with a white hatch
FLAT ROOF
Plasterboard - 12.5 mm

¹ According to the Danwood production standard in force at the time of manufacture.

² The roof cross section may change due to construction standard requirements and type of coverin.

DAN-WOOD garages are delivered together with houses. Installation of foundation slab, screed and services incoming to the slab are supplied by the customer.