

# GARAGES – STANDARD OF FINISH

| STANDARD GARAGE WITHOUT FOUNDATIONS   |  |
|---|--|
| EXTERNAL WALL   |  |
| Render, colour white  |  |
| Thermal insulation, facade polystyrene 50 mm  |  |
| OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm <sup>1</sup>   |  |
| Timber studs (resinous wood) 120 mm   |  |
| EXTERNAL WALL CLOSE TO HOUSE'S WALL   |  |
| OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm <sup>1</sup>   |  |
| Timber studs (resinous wood) 120 mm   |  |
| INTERNAL WALL   |  |
| OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm <sup>1</sup>   |  |
| Timber studs (resinous wood) 120 mm   |  |
| EAVES CLADDING  |  |
| Timber cladding, colour white   |  |
| PENT /GABLE /HIPPED ROOF  |  |
| Cement roof tiles according to the samples <sup>2</sup>   |  |
| Roof battens  |  |
| Counter battens   |  |
| Breathable membrane   |  |
| Timber rafters/trusses (according to the static calculations)   |  |
| OSB sterling boards/chipboards 22 mm, with access opening   |  |
| FLAT ROOF   |  |
| Gravel ballast with min. thickness 50   |  |
| EPDM  |  |
| Tapered panels of mineral wool  |  |
| OSB sterling boards/chipboards 22 mm  |  |
| Timber joists 220 mm  |  |
| GUTTERING   |  |
| PVC gutters and down pipes, colour white  |  |
| GARAGE DOOR   |  |
| Single garage: sectional garage door, manual drive, woodgrain finish, according to the samples, 2500 x 2125 mm, colour white                  |  |
| Double garage: sectional garage door, automatic, woodgrain finish, according to the samples, 5000 x 2125 mm, colour white (if drawn on plans) |  |
| GARAGE SIDE DOOR  |  |
| Colour white (if drawn on plans)  |  |

## OPTIONS

The elements of the options below are only valid if the option is selected and the associated surcharge is accepted.

### OPTION 1

Shelves between timber studs on external and internal walls

### OPTION 2A

Electrical installation for a garage integrated with the house: 2 ceiling cable outlets with 1 two-way switch, 2 single electric sockets.

### OPTION 2B

Electrical installation for a detached garage: 2 ceiling cable outlets with 1 two-way switch, 2 single electric sockets, 6 way consumer unit, electrical cable between house and garage (distance between outlets in foundation - max 10 m) with connection. Notes: Customer is responsible for supply and installation of electrical cable duct between house and garage. Electrical equipment in garage can differ from the one installed in a house.

### OPTION 3

Electric drive for garage gate 2500 x 2125 mm

### OPTION 4

Door between house and garage

### OPTION 5

Internal linings (for garages larger than 40 m<sup>2</sup> included in the price)

#### EXTERNAL WALL

Insulation - mineral wool (between wall studs)- 120 mm

OSB sterling board/chipboard - 12 mm or gypsum fibre board 12.5 mm <sup>1</sup>

Plasterboard - 12.5 mm

#### PENT /GABLE /HIPPED ROOF

Mineral wool above bottom chord truss 220 mm

Plasterboard - 12.5 mm

with folding loft ladder to attic area with a white hatch

#### FLAT ROOF

Battens

Plasterboard - 12.5 mm

<sup>1</sup> According to the Danwood production standard in force at the time of manufacture.

<sup>2</sup> The roof cross section may change due to construction standard requirements and type of coverin.

DAN-WOOD garages are delivered together with houses. Installation of foundation slab, screed and services incoming to the slab are supplied by the customer.